

CSI 2130 Machinery Health Collector

- High-speed data collection covers more machines in less time
- Embedded PeakVue® technology makes you a bearing and gear analysis expert
- In-field alarming identifies problem machinery immediately
- Splash proof, dustproof, and sealed IP-65 enclosure is safe for most environments
- Unlimited memory storage can handle all necessary data
- Easily upgradeable to higher functionality to grow with your program



Early detection of critical machine defects allows plant personnel to plan and prioritize maintenance corrective action to avoid costly interruptions in production schedules.

Introduction

Emerson is proud to be the leader in the development of advanced Machinery Health Management technologies. With that in mind, Emerson has rounded out its line of portable vibration products with the new CSI 2130 Collector. This portable vibration data collector is just the right size for getting new programs off the ground or contributing to existing programs and is able to grow in functionality as needed so your investment is never limited to today's needs.

Product Description

Emerson's CSI 2130 Machinery Health Analyzer is already

recognized worldwide as the fastest, highest-performance portable vibration analyzer on the market. The unit's multi-functional, handheld platform is based on a module design that allows any combination of technology options:

- Route data collector
- In-field vibration analyzer
- Field balancing instrument
- Laser alignment tool
- Transient collector
- Advance Vibration Analysis



The CSI 2130 Collector features the same speed and ease-of-use functionality as the CSI 2130 Analyzer.

The new CSI 2130 Collector is built on the same modular design capability of the CSI 2130 Analyzer, but is offered as a dedicated vibration route data collector. The functionality of this instrument, combined with its ability to upgrade, makes this data collector ideal for facilities that:

- Are launching a predictive maintenance program.
- Have a limited budget, but want the best data collection capability for their money.
- Operate small- to medium-sized plants with less machinery to monitor.
- Are larger plants looking to expand existing vibration data collection coverage.

Full-Featured Data Collection

The CSI 2130 Collector is a full-featured vibration data collector available at an affordable price. When integrated with AMS™ Suite: Machinery Health Manager, the CSI 2130 Collector is the most

capable and complete portable vibration route data collector available.

Fastest Data Collection Available

The CSI 2130 Collector has the same fast data collection speed as the CSI 2130 Analyzer. This speed allows you to cover 30-60% more plant assets in the same amount of time as other data collectors could. Speed does not sacrifice quality – data collected will be high resolution and Fmax with vibration spectrum, waveform, and up to 12 specific narrow bands of trend data for machine health analysis.

PeakVue Analysis

The patented PeakVue digital stress wave detection technology, standard with the CSI 2130 Collector, is recognized as the most accurate provider of early detection of bearing and gear defects available in a portable vibration data collector.

Easy Operation

The 640x480 pixel, full VGA color screen provides a viewing area large enough to effectively review data in the field, while collecting data in live mode or with an active cursor after collection. The screen viewing area can also be divided to show multiple plots, analysis parameters with the data plots, or in-field reports. The CSI 2130 Collector's large buttons and intuitive navigation screens make the instrument easy to use, even when wearing gloves.

In-Field Alarming

The CSI 2130 Collector receives the vibration parameter alarm levels during download of the collection route, so a notification appears immediately on screen with developing faults at the time of measurement. The machine can then be flagged for further analysis from the field with a single button.

Upgradeable to Higher Functionality

As part of the modular CSI 2130 platform, the CSI 2130 Collector can grow with your predictive maintenance needs and experience to include any of the program modules found in the CSI 2130 Analyzer.

Service Options

Emerson offers options for getting started with your CSI 2130 Collector or CSI 2130 Analyzer. Whether you are launching a program or revitalizing an existing program, our experts are available to help you incorporate the technology into your maintenance program and maximize your investment as quickly as possible.

Technical Specifications

Data Analysis Speed

400 line / 1000 Hz spectrum: 0.14 sec/avg
1600 line / 1000 Hz spectrum: 0.5 sec /avg

Analysis Capabilities

Noise Floor

- Less than 0.2 micro-volts per root Hz over 1,000 Hz frequency range

PeakVue

- Built-in, with selectable filters

Demodulation

- Built-in, with selectable filters

SST

- Built-in Low Frequency processing

Dynamic Analysis

- Overall, Spectra, Waveform, 12 analysis parameters, 1/3 Octave, A-weighting, Phase

Signal Range

- Autoranging maintains optimum dynamic range. 16 bit A/D Converter has 96 dB Dynamic Range (coupled with analog integration provides better than 120 dB for typical applications).

Frequency Range

- 740 ranges from DC-10 Hz to DC-80 kHz

Low Frequency Response

- DC coupling on non-powered inputs allows flat response to DC for non-integrated signals.

Resolution

- 1/3 Octave, 100, 200, 400, 800, 1600, 3200, 6,400, 12,800 lines.

Averaging

- Normal, Peak Hold, Order Tracking, and Synchronous Time

Number of Averages

- 5,000 in Route mode

Integration

- None, Single, Double (Analog or Digital)

Trigger

- Tach

Anti-Aliasing

- Filters attenuate all alias components to below noise floor.

Amplitude Units

- Metric or English, acceleration, velocity, displacement, or user programmable

Frequency Units

- Hz, CPM, Orders

Scaling

- Linear or Log, both X and Y axes

Windows

- Hanning or Uniform

Cursor

- Single, Harmonic, Moving Harmonic, Sideband

Memory

80 MB total

- 32 MB for programs and data storage (expandable with off-the-shelf Flash RAM cards)
- 16 MB for operating system

Signal Inputs

Powered Inputs

- 2 mA, +20 V ICP power supply, +/- 15 V

Non-Powered Inputs

- +/- 24 V range

Input Impedance

- Greater than 125 k ohms

Tach

- NTTL input, built-in conditioning for non TTL signals, adjustable trigger

Pseudo tach

- Generates tach pulses for hidden shafts

Triaxial

- Internal multiplexer for automatic sequencing of triaxial measurements

Output

Communication with Host Computer with USB, Ethernet, Serial, or Email data files.

Physical Data

Color Display

- 5.75" x 4.25" (146 mm x 108 mm)
- Transflective (for indoor or outdoor use)
- Liquid crystal display
- Built-in backlight
- 640 x 480 pixel

Height:

- 8" (203 mm)

Depth:

- 1.88" (48 mm)

Width

- 10.25" (260 mm)

Weight

- 4.5 lbs (2.04 kg)

Operating Conditions

Moisture

- Sealed enclosure, IP-65 rated

Temperature

- 15 to 122 °F (-10 to 50 C)

Power Supply

Battery

- NiMH Capacity: 4.5 amp hours

Voltage

- 7.2 V

Battery Life

- 8 hours typical use (longer with backlight off). Data saved in the event of low battery voltage.

Charger

- Discharge/Fast charge/Trickle charge "Smart Charger." Also functions as a continuous power supply.

Recharge Time

- 3 hours

Standard Accessories

- 1 Accelerometer
- 1 Coiled sensor cable
- 1 Magnet mount
- Power supply
- USB Communication cable
- Firmware/instructional CD
- Storage case

Localized Languages

The CSI 2130 Collector is available in: English, Spanish, French, German, Russian, Finnish, Swedish, Turkish, and Chinese.

Safety and Industrial Ratings

Designed for use in industrial environments, the CSI 2130 Collector has received an IP65 rating certifying that it is dust- and splash water tight. It is also certified to comply with international safety standards in the United States, Canada, and Europe for hazardous areas.

Safety rated versions A2130D1Q and A2130D1Q-CU are available for the following hazardous environments:

FM

- Class I, Division 2, Groups A, B, C and D, Temperature Code T4A @ Ta = 50C, CLI, Zone 2, IIC, Non Incendive, T4

CSA

- Class I, Division 2, Groups A, B, C and D, Temperature Code T4A @ Ta = 50C Ex nA IIC, T4 @ Ta = 50C

ATEX

- CE EX II 3 G
- Ex nL IIC T4



Upgrade Matrix for Model A2130D1

Model	Description
A2130D1-UP-A1	Upgrade package from A2130D1 to A2130A1
A2130V2	Add Second Channel*
A2130S3	Add Advanced Cross Channel Firmware*
A2130S4	Add Transient Firmware*
A2130S5	Add ODS/Modal Firmware*
A2130S7	Add Balancing Firmware
A2130S8	Add Basic Alignment Firmware
A2130S9	Add Advanced Alignment Firmware
A8730EZ	Basic Laser Expansion Pak with 10x10 targets and RF communication
A8730EZ-IN	Basic Laser Expansion Pak with 10x10 targets and cabled communication
A873015-CU	Advanced Laser Expansion Pak with 10x10 targets and RF communication
A873015-IN	Advanced Laser Expansion Pak with 10x10 targets and cabled communication
A873025-CU	Advanced Laser Expansion Pak with 20x20 targets and RF communication
A873025-IN	Advanced Laser Expansion Pak with 20x20 targets and cabled communication

* Second Channel, Advanced Cross Channel, Transient, and ODS/Modal options require an upgrade to the CSI 2130 Analyzer.

**Emerson Process Management
Asset Optimization Division**

835 Innovation Drive
Knoxville, TN 37932
T (865) 675-2400
F (865) 218-1401

©2007, Emerson Process Management.

The contents of this publication are presented for informational purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice.

All rights reserved. PlantWeb, AMS, Machinery Health and PeakVue are marks of one of the Emerson Process Management group of companies. The Emerson logo is a trademark and service mark of Emerson Electric Co. All other marks are the property of their respective owners.



Online Machinery Health Management powers PlantWeb through condition monitoring of mechanical equipment to improve availability and performance.